



Compatible with
ADJ RFC
(Sold Separately)
1223200026



Compatible with
ADJ RFC
(Sold Separately)
1223200026



WiFLY EXR QA5 IP

1226100292

WiFLY EXR HEX5 IP

1226100293



Specification

- Light Source: 5x 5-Watt QUAD LEDs (Red, Green, Blue & Amber)
- Smooth RGBA color mixing
- 5 DMX Channel modes: 4, 5, 6, 10 or 11 channel modes
- 5 Operational modes
- IP65 & Outdoor Rated
- Rechargeable Lithium battery powered, with wireless DMX,
- Built-in WiFLY wireless DMX: compatible with ADJ's WiFLY Transceiver (sold separately)
- Extended wireless range - up to 2500 ft/760m
- Battery Life: Up to 20hrs
- Power Draw: 35W total (All LED's @ Full On)
- Multi-voltage operation: AC 100-240V, 50/60Hz
- Dimensions (LxWxH): 10" x 7.5" x 11.75" in. / 254 x 190.5 x 299.5 mm
- Weight: 9.25 lbs. / 4.2 kg

Specification

- LED Source: 5x 10-Watt HEX LEDs (Red, Green, Blue, White & Amber + UV)
- Rechargeable Lithium battery powered, with wireless DMX, IP65, & Outdoor Rated
- Built-in WiFLY wireless DMX: compatible with ADJ's WiFLY Transceiver (sold separately)
- Extended wireless range - up to 2500 feet/760m
- 5 DMX Channel modes: 4, 5, 6, 10 or 11 channel modes / Beam angle: 25-degree
- 6 Operational modes: Static Color; RGBAW + UV Dimmer Mode; Color Change; Color Fade; Auto Run (Program Run); and DMX Controlled
- 16 Color Change Modes / 16 Color Fade Modes / 64 built-in Color Macros
- LED pulse and strobe effect / Flicker Free Operation / Electronic Dimming: 0 - 100%
- 4-Pin Power AC IN/OUT outlets on rear to daisy chain power (up to 11 units)
- Power Draw: 50W total (All LED's @ Full On)
- Multi-voltage operation: AC 100-240V, 50/60Hz
- Dimensions (LxWxH): 12.25" x 11" x 7.5" / 310 x 280 x 194mm
- Weight: 12 lbs. / 5.48 kg
- Battery Life: Up to 16hrs

RGBA Color Mixing:



RGBAW Color Mixing + UV:



Photometric

R	D25	1596	676	362	170	130	(LUX)
G	D25	2130	685	329	177	117.3	
B	D25	2210	641	277	121.7	78.4	
A	D25	2170	633	399	170	106.9	
RGBA	D25	8200	2480	1078	554	357	



Photometric

R	D40	971	237	97.8	48.9	32.1	(LUX)
G	D40	951	257	108.5	55.7	37.5	
B	D40	815	217	85	53.1	31.7	
W	D40	1190	302	113.8	67.6	42.3	
A	D40	574	140	50.6	28.9	17.6	
UV	D40	179	47.7	18.3	10.9	6.5	
RGBAW+UV	D40	4240	966	449	241	154.5	

