



**12P HEX/12P HEX PEARL**

**5P HEX/5P HEX PEARL**



**Specification**

- Light Source: 12x 12-Watt RGBAW + UV LEDs, (Rated at approximately 50,000 hrs.)
- 4 DMX Modes: 6, 7, 8, & 12 channel
- 5 Operational modes: Static Color Mode, RGBAW & UV Dimmer Mode, Program Mode, Sound Active Mode and DMX Controlled
- 7 Built-In Programs / 63 built-in Color Macros / Flicker Free operation
- 5 selectable Dimmer Curves (Standard, Stage, TV, Architectural & Theatre)
- Beam angle: 30-degree
- Compatible with Dotz Par RF wireless remote control (sold separately)
- Power link via IEC power cables. (6x 12P Hex's Max @ 110V, 13x 12P Hex's Max @ 240V)
- Power Draw: 150W total (All LED's @ Full On)
- Multi-voltage operation: AC 110-250V, 50/60Hz (IEC power In/Out)
- Dimensions (LxWxH): 11.75" x 10" x 5.5" / 298 x 249 x 136mm
- Weight: 9 lbs. / 3.9 kgs

**Specification**

- Light Source: 5 x 10-Watt RGBAW + UV LEDs, (Rated at approximately 50,000 hrs.)
- Smooth RGBAW + UV color mixing
- 4 DMX Modes: 6, 7, 8, & 12 channel
- 5 Operational modes: Static Color Mode, RGBAW & UV Dimmer Mode, Program Mode, Sound Active Mode and DMX Controlled
- 7 Built-In Programs / 63 built-in Color Macros
- 5 selectable Dim Curves (Standard, Stage, TV, Architectural & Theatre)
- Compatible with Dotz Par RF wireless remote control (sold separately)
- Data linkable via 3-pin XLR cables / Power linkable via IEC power cables
- Power Draw: 60W total (All LED's @ Full On)
- Multi-voltage operation: AC 100-240V, 50/60Hz (IEC power In/Out)
- Dimensions (LxWxH): 8.25" x 4" x 8.75" / 210 x 100 x 220mm
- Weight: 5 lbs. / 2 kgs

RGBAW Color Mixing + UV:




RGBAW Color Mixing + UV:



**Photometric**

|            |          |       |      |      |     |     |       |
|------------|----------|-------|------|------|-----|-----|-------|
|            | R        | 1024  | 312  | 150  | 85  | 55  |       |
|            | G        | 2180  | 641  | 305  | 172 | 112 |       |
|            | B        | 2990  | 305  | 376  | 217 | 135 |       |
| Beam Angle | W        | 3620  | 810  | 428  | 247 | 162 | (LUX) |
|            | A        | 1195  | 961  | 179  | 104 | 70  |       |
|            | UV       | 442   | 384  | 83   | 38  | 28  |       |
|            | RGBAW/UV | 10890 | 2770 | 1330 | 733 | 455 |       |



**Photometric**

|            |          |      |      |     |     |     |       |
|------------|----------|------|------|-----|-----|-----|-------|
|            | R        | 562  | 152  | 70  | 40  | 27  |       |
|            | G        | 1121 | 300  | 136 | 76  | 49  |       |
|            | B        | 1030 | 283  | 130 | 75  | 48  |       |
| Beam Angle | W        | 1544 | 410  | 187 | 101 | 66  | (LUX) |
|            | A        | 387  | 100  | 45  | 28  | 20  |       |
|            | UV       | 313  | 81   | 37  | 21  | 14  |       |
|            | RGBAW/UV | 4420 | 1220 | 581 | 318 | 210 |       |

