

# Multipar MSR 575 PRO

NEW

**AMLUX**<sup>®</sup>

Cod: **PP#000000305** BLACK (GLASS REFLECTOR)

Cod: **PP#000000804** GREY (GLASS REFLECTOR)

The PRO version features split ballast and is especially designed for shows and exhibitions where the ballast needs to be hidden. Also Truss load can be reduced, setting up the ballast e.g. on the floor instead of next to the multipar.

The Multipar MSR575 PRO is the right choice for all events where daylight (6000K) is needed to light up stages and theatres.

- Superb distribution
- Smooth soft edge
- Build out of sturdy aluminum.
- Easy to use and maintain
- Ballast in separated housing
- Powercon connector
- Split lamp ballast
- Different lenses for varying the beam
- 4 lenses included in delivery (very narrow, narrow, medium flood, wide flood)
- high tech glass reflector

## RACCOMANDED LAMPS

Cod: **LA#22021131800** MSR 575/2 PHILIPS 575W GX9,5 7200°K 1000ore

Cod: **LA#1 2011132302** HSR 575W/60 OSRAM 575W 95V GX9,5 6000°K 1000ore

## TECHNICAL SPECIFICATIONS

Power supply:	AC 230V, 50Hz
Power consumption:	600W
Lamp body (LxWxH):	335 x 230 x 340 mm
Ballast (LxHxW):	245 x 140 x 255 mm
Weight net(ballast+ lamp body):	8,3kg + 4,7kg
Fitting lamp:	MSR Metal Halide Lamp, GX9,5
Maximum ambient temp.:	25°C
Maximum housing temp.:	140°C
Minimum distance:	2 mt
Lenses kit:	190 x 19 x 75 mm

## PHOTOMETRICAL DATA

