



Cromato / Silver:

- Cod. **SG#20190201** 19 °
- Cod. **SG#20260201** 26 °
- Cod. **SG#20360201** 36 °
- Cod. **SG#20500201** 50 °

Accessories:

- IRIS01** Iris
- PB#0001501** Reflector
- PG#900300** Colourframe BLACK
- PG#900200** Colourframe CHROME
- GOBO01** Goboholder
- KT#006001** KIT Electronic Ballast 150W CDM-T / HCI-T G12 Black
- KT#006002** KIT Electronic Ballast 150W CDM-T / HCI-T G12 Grey

Nero / Black:

- Cod. **SG#20190301** 19 °
- Cod. **SG#20260301** 26 °
- Cod. **SG#20360301** 36 °
- Cod. **SG#20500301** 50 °

Accessori:

- IRIS01** Diaframma
- PB#0001501** Parabola
- PG#900300** Portagelatina NERO
- PG#900200** Portagelatina CROMATO
- GOBO01** Portagobo
- KT#006001** KIT Ballast Elettronico 150W CDM-T / HCI-T G12 Nero
- KT#006002** KIT Ballast Elettronico 150W CDM-T / HCI-T G12 Grigio

Features:

- Independent lamp alignment controls.
- High-impact, thermally insulated knobs and shutter handles.
- Rotating shutter assembly for keystone angles.
- Heavy-gauge stainless steel shutter.
- Lens secured with silicone shock free.
- Sturdy gel frame holders with two accessory slots.

Descrizione:

- Regolazione allineamento lampada indipendente.
- Manopole e maniglie termicamente isolate.
- Corpo in alluminio.
- Obiettivo fissato in 2 punti, la lente appoggia su supporti in silicone per evitare la rottura.
- Due robusti supporti per portagelatina o accessori vari.

Specifications :

- **Voltage:** 120/240v 50/60Hz
- **Dimension:** 505x340x340mm
- **Weight:** 5.2Kg
- **Lamp:** 575W HPL / 600W GKV
- **Active power:** 600V.A.

Lenses : 19° - 26° - 36° - 50°

Dati tecnici:

- **Volt:** 120/240v 50/60Hz
- **Dimensione:** 505x340x340mm
- **Peso:** 5.2Kg
- **Lampada:** 575W HPL / 600W GKV
- **Assorbimento:** 600V.A.

Lenti : 19° - 26° - 36° - 50°

KIT BALLAST ELETTRONICO CDM-T/ HCI-T 150W

AMLUX[®]

KIT BALLAST ELETTRONICO CDM-T/ HCI-T 150W



Cod. **KT#006002** GRIGIO / GREY

Features:

This technological electronic ballast kit is to be added to our products ; PAR HPL and PROFILE. Endowed with microprocessor which controls the power input, eliminates all visible flickering of the lamps, prolongs the lifetime of the lamp with 30 %, with an energy saving of 20%. Very compact and light, it's an optimal product for transforming your halogen projectors into metal halide.

Cod. **KT#006001** NERO / BLACK

Descrizione:

Il tecnologico Kit Electronic Ballast viene applicato ai nostri prodotti HPL, è dotato di microprocessore che ne controlla l'alimentazione, elimina i fenomeni di sfarfallio visibili dalle lampade oltre che allungare la vita media delle stesse del 30% con un risparmio di energia del 20%. Molto compatto e leggero è un'ottimo prodotto per trasformare i vostri proiettori da alogeni a ioduri metallici.

Specifications :

- **Voltage:** 220/240v 50/60Hz
- **Dimension:** 205x57x104mm
- **Weight:** 1 Kg
- **Lampholder:** G12
- **Lamp:** CDM-T / HCI-T 150W
- **Active power:** 170 V.A.
- **Fuse:** 2 A

Dati tecnici:

- **Volt:** 220/240v 50/60Hz
- **Dimensione:** 205x57x104mm
- **Peso:** 1 Kg
- **Portalampada:** G12
- **Lampada:** CDM-T / HCI-T 150W
- **Assorbimento:** 170 V.A.
- **Fusibile:** 2 A