

## Applications

Beam style	variable-spread, soft-edged beam
Suitable for	large scale theatre
Specification level	professional range
Beam angle	10° - 70°
Typical throw distance	3-20m

## Electrical specifications

Supply volts	230/240V AC single phase
Max. lamp Watts	2500W
Lamp-base	G22 standard, GY16 on request
Auto-disconnect	double-pole microswitch
Cable/connection	1.5m, 3 x 2.5mm <sup>2</sup> flexible cable to bare ends
Standard compliance	EN60598-2-17, CE marked

## Mechanical specifications

Paint finish	black epoxy power paint
Lamp house construction	extruded aluminium and sheet steel
Reflector	87mm, diameter glass
Lens	Ø200mm pebble convex
Mounting & Suspension	pole-operated stirrup with DIN spigot for the control of pan and tilt movement

Rear handle	yes
Weight/ packed weight	10.4 kg / 13.6 kg
packed volume	0.10 m <sup>3</sup>
Filter cut size	245x 245mm
Accessory runners	3 slots
Safety guards	included
Colour frame	metal, 245x245mm, supplied
Lamp access	hinged base
Lens access	front and via lamp access

## Operational specifications

Focus adjustment	screw focus with front and rear control
Working position	max. tilting ±90° from horizontal
Beam Shaping	using barndoor accessory
Positional	single rim-clamp tilt lock

## Lamp type

2000W G22	CP55/ CP75 3200K 480hrs, CP92 3200K 400hrs
2000W GY16	CP72 3200K 480 hrs
2500W G22	CP91 3200K 400 hrs

LDR recommends Philips lamps

## Accessories

Spare metal colour frame	20100107
Spare safety guard	20100207 safety bond 20101207
4-leaf barndoor	20100307
Hock clamp	20101000 Alu-grip clamp 20101100
Colour scroller Xpress 26	20106026 with mounting plate 20600007

## Photometric Data

Spot focus	CP75									
	1.9	2.0	2.2	2.4	2.5	2.7	2.8	3.0	3.1	m
BeamØ	1.9	2.0	2.2	2.4	2.5	2.7	2.8	3.0	3.1	m
lux	1563	1331	1148	1000	879	779	694	623	563	
Distance	12	13	14	15	16	17	18	19	20	m

Flood focus											
	4.2	5.6	7.0	8.4	9.8	11.2	12.6	14.0	15.4	m	
BeamØ	4.2	5.6	7.0	8.4	9.8	11.2	12.6	14.0	15.4	m	
lux	2200	1238	792	550	404	309	244	198	164		
Distance	3	4	5	6	7	8	9	10	11	m	

LUCI DELLA RIBALTA PROFESSIONAL LIGHTING PRODUCTS

# TONO<sup>®</sup> F2000 plus P.O.

## 2000 - 2500W

### pole-operated fresnel

part number: 12901000




Compact, lightweight and multi-featured 2/2.5KW pc spotlight for larger venues.

It features an extremely wide beam angle and includes a front hinging lamp tray, a robust G22 lamp-base, screw focus, strong tilt lock and double-microswitch interlock for safe lamp replacement.

A colour frame, safety guard and 1.5m mains cable are included as standard.

**On request also available with GY16 lamp-base**



Distributed by:  
**AMLUX s.r.l.**  
 Via Belgio, 11/13  
 46042 Castel Goffredo (MN), Italy  
[www.amlux.it](http://www.amlux.it) [info@amlux.it](mailto:info@amlux.it)