

CYC LED 300 RGBW DMX



Luminaire: Cyclorama, LED, 300W, RGBW DMX control



Type

Green line

Family

Floodlight

Source

LED RGBW

Power

300W

Control

DMX-RDM

Connectors

Powercon® In&Out

Voltage

90-260V, 50-60Hz

Product sizes

15Kg

Pack sizes

565mm x 615mm x 320mm

0.111m³

IES/LDT

Available on website

DWG

Available on website

User manual

Available on website

Video

(http://www.youtube.com/watch?v=_7NbVnY8ktE)

Technical features

- Aluminum housing for high heat dissipation by natural ventilation
- Adjustable forced ventilation
- Yoke with clutch-locking system
- PO version on request, with 2-way pole operation for tilt and pan
- ARC version on request, with 2-way DMX control of tilt and pan


Functional features

- LED temperature range control to guarantee the best performances
- Colour temperature (CCT) adjustment
- Built-in memory for storage and playback of scenes and cues
- Constant colour temperature during the whole dimming curve
- Silent mode function
- Zero to Full dimming with pre-loaded dimming curves
- Flicker-free mode with adjustable PWM LED frequency for best use with cameras
- Strobe function with adjustable frequency
- Master/Slave mode
- Remote controllable functions via DMX-RDM
- 8/16 bit control mode on all channels
- "Hue/Saturation/Intensity" (HSI) configuration mode
- "Cyan/Magenta/Yellow" (CMY) configuration mode
- Cooling system with high efficient heat sink


Green line advantages

- No dangerous UV or IR rays for the safe lighting of the people and objects
- No radioactive or mercury-based components
- Nearly 75% saving on mains power consumption if compared to an equally-performing conventional fixture
- Reduced installation and cabling costs thanks to the In&Out chain connection system both for power mains and DMX/DALI data control
- Savings on running costs thanks to the extended lifespan of the LED source compared to the periodical replacement of conventional bulbs
- Savings on the air-con set up and supply, thanks to the lower heat emission of the fixtures
- No maintenance costs for the replacement of colour filters due to overheating and damage

Sizes (in mm)



Light output diagram



Accessories

DOU-00001513

FUNE

Acc: Safety net with spring hook

GAC

Acc: Hook clamp for 40/50mm tube

HC/300 S

Acc: Half swivel coupler 300kg max

PO/2 CYC300

Yoke: Pole Operated for Pan-Tilt

