

PR LED 50 ZS CW DMX



Luminaire: Profile, LED, 50W, CW
zoom 20°-40°, 5600K, DMX control



Type

Green line

Family

Profile

Source

LED Cool White

Power

50W

Control

DMX-RDM

Colour temperature

5600K

Cri

>90

Connectors

Cable without plug

Voltage

90-260V, 50-60Hz

Product sizes

4.1Kg

Pack sizes

255mm x 615mm x 260mm

4.6Kg

0.041m³

IES/LDT

Available on website

DWG

Available on website

User manual

Available on website

Technical features

- Aluminum housing for high heat dissipation by natural ventilation
- Adjustable forced ventilation
- Independent and removable shutter blades for beam shaping
- Filter frame lockable top cover
- Gobo-holder slot
- Soft and smooth lens focusing adjustment
- Yoke with clutch-locking system
- Adjustable yoke for fixture balancing


Functional features

- LED temperature range control to guarantee the best performances
- Constant colour temperature during the whole dimming curve
- Remote controllable functions via DMX-RDM


Green line advantages

- No dangerous UV or IR rays for the safe lighting of the people and objects
- No radioactive or mercury-based components
- Nearly 75% saving on mains power consumption if compared to an equally-performing conventional fixture
- Reduced installation and cabling costs thanks to the In&Out chain connection system both for power mains and DMX/DALI data control
- Savings on running costs thanks to the extended lifespan of the LED source compared to the periodical replacement of conventional bulbs
- Savings on the air-con setup and supply, thanks to the lower heat emission of the fixtures
- No maintenance costs for the replacement of colour filters due to overheating and damage

Sizes (in mm)



Light output diagram



Accessories

FUNE

Acc: Safety net with spring hook

HC/075

Acc: Half swivel coupler 75kg max

MINI GAC

Acc: Hook clamp for 30mm tube

PGM MZ O

Acc: M size adjustable gobo-holder

TC MINI

Acc: Colour frame