VD LED 450 WW DMX

Luminaire: Followspot, LED, 450W, WW zoom 08°-19°, 3200K, DMX control



Type

Green line

Family Followspot

Source

LED Warm White

Power

Control DMX-RDM

Colour temperature

Cri > 95

Connectors

Powercon® In&Out

Voltage 90-260V, 50-60Hz

Product sizes

23.8Kg

Pack sizes 1175mm x 420mm x 460mm 0.227m³

DWG

Available on website

User manual Available on website

Video (http://www.youtube.com/watch? v=dWsCn9GD_BQ)

Technical features

- · Aluminum housing for high heat dissipation by natural ventilation
- Adjustable forced ventilation
- Filter frame lockable top cover
- Gobo-holder slot
- Soft and smooth lens focusing adjustment
- Yoke with clutch-locking system
- Adjustable yoke for fixture balancing


Functional features

- LED temperature range control to guarantee the best performances
- Constant colour temperature during the whole dimming curve
- Silent mode fuction
- Zero to Full dimming with pre-loaded dimming curves
- Flicker-free mode with adjustable PWM LED frequency for best use with cameras
- Strobo function with adjustable frequency
- Master/Slave mode
- Remote controllable funcions via DMX-RDM
- 8/16 bit control mode on all channels
- Cooling system with high performance heat pipes


Green line advantages

- No dangerous UV or IR rays for the safe lighting of the people and objects
- No radioactive or mercury-based components
- Nearly 75% saving on mains power consumption if compared to an equally-performing conventional fixture
- Reduced installation and cabling costs thanks to the In&Out chain connection system both for power mains and DMX/DALI data control
- Savings on running costs thanks to the extended lifespan of the LED source compared to the periodical repalcement of conventional bulbs
- Savings on the air-con setup and supply, thanks to the lower heat emission of the fixtures
- No maintenance costs for the replacement of colour filters due to overheating and damage

Sizes (in mm)



Light output diagram



Accessories

BS Acc: Low stand, DIN, lazy leg

CGP2 Acc: 3-section Wind-Up Stand, laz y leg
CMA 12 E Acc: Manual 6-colour colour changer
CTRL 6CH MEM Acc: 6-ch DMX consolle with memories
DIN P 10 Acc: TV spigot / M10 adapter with plate

RF Acc: Wheel set with brake

