

PRODUCT DATASHEET

HALOSTAR 24 V 20 W 24 V G4

HALOSTAR 24 V | Low-voltage (24 V) pin based halogen lamps



PRODUCT BENEFITS

- Base pins are tempered to protect against corrosion
- Axial filament ensures optimum directional light
- High illuminance level
- Contains no mercury

TECHNICAL DATA

Electrical data

Nominal wattage	20.00 W
Nominal voltage	24 V
Rated wattage	20.00 W
Power factor λ	1.00


Photometrical data

Nominal luminous flux	320 lm
Rated color temperature	2900 K
Light color (designation)	Warm White
Rated luminous flux	320 lm
Color rendering index Ra	100
Lumen main.fact.at end of nom.life time	0.80
Color temperature	2900 K
Luminous flux	320 lm
Color rendering index Ra	100

Light technical data

Starting time	0.0 s
Warm-up time (60 %)	0.00 s

Dimensions & weight



Diameter	10.0 mm
Overall length	33.0 mm
Light center length (LCL)	22.0 mm
Outer bulb	T10
Length	33.0 mm
Maximum diameter	10.0 mm

Distributed by:

AMLUX s.r.l.

46042 Castel Goffredo (MN)

info@amlux.it - www.amlux.it

Lifespan

Nominal lamp life time	1000 h
Rated lamp life time	1000 h
Number of switching cycles	25000

Additional product data

Base (standard designation)	G4
Mercury content	0.0 mg
Mercury-free	Yes
Product remark	Quick-acting miniature fuse needed acc. to EN60432-3

Capabilities

Burning position	Any
Dimmable	Yes


Certificates & standards

Energy consumption	22 kWh/1000h
Energy efficiency class	C

Country-specific categorizations

ILCOS	HSG/C/UB-20-24-G4-10/22
-------	-------------------------

Light Distribution



Spectral power distribution

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075177901	Folding carton box 1	25 mm x 23 mm x 70 mm	3.00 g	0.04 dm ³
4058075177918	Shipping carton box 40	144 mm x 107 mm x 121 mm	164.00 g	1.86 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.