## Product datasheet

### Article no.: 847009

LED Bar / Tube, 2835 SMD 2800, IP 55



### **Technical Data**

| Dimensions & Weight        |        |
|----------------------------|--------|
| Length                     | 900 mm |
| Width                      | 17 mm  |
| Height                     | 10 mm  |
| Product weight             | 148 g  |
| Cutting possibility (each) |        |



#### **Electrical Characteristics**

| Power / power consumption   | 10,50 W / 10,50 W         |
|-----------------------------|---------------------------|
| Input voltage               | 24V DC                    |
| Input current               |                           |
| Connection possibility      | plug-in power supply unit |
| Protection class I, II, III | III                       |

### Light Technical Data

| Colour Designation | warmwhite |
|--------------------|-----------|
| Colour temperature | 2800 K    |
| Luminous Flux      | 900 lm    |
| Beam angle         | 120°      |
| LED type           | SMD 2835  |
| LED quantity       | 90        |

#### Absolute maximum ratings

The LED will get damaged and the lifetime will decrease when you overrun absolute maximum ratings.

| Working temperature | -5°C - +40°C  |  |  |  |  |
|---------------------|---------------|--|--|--|--|
| Storage temperature | -10°C - +60°C |  |  |  |  |
| IP - Code           | IP 55         |  |  |  |  |



15.11.2017 Errors and technical data are subject to change without notice.

# Product datasheet

# Article no.: 847009

| LED Bar /      | Tube, 2835 SMD   | 2800, IP 55   |                                      | 10.      |            | 18      |         |                           |
|----------------|--|---|--------------------------------------|----------|------------|---------|---------|---------------------------|
| kap            | 290<br>LED   |   |                                      | 10.5mm   | <b>b</b> . | 3.5mm   |         |                           |
| General p      | roduct data  |   |                                      |          |            |         |         |                           |
| Environmer     | ntal Characteristics   |   |                                      |          |            |         | 3       |                           |
| Energy Label   |  | A+  |                                      |          |            |         | 1       |                           |
| Energy consu   | mption   | 11 kWh/1000h  |                                      |          |            |         | Ē       |                           |
| Lifespan       |  |   |                                      |          |            |         |         |                           |
| Lamp life time |  | 30000 h   |                                      |          |            |         | :       | . 9                       |
|                | end of lifetime  | 0,70  |                                      |          |            |         | m       | 900mm                     |
| Number of swi  | tching cycles  | 100000  |                                      |          |            |         | Ξ       | Ì                         |
|                |  |   |                                      | 10mm     |            | 17mm    | -       |                           |
|                |  |   |                                      |          |            | D       | 1       |                           |
|                |  |   |                                      |          |            |         | 3       |                           |
|                |  |   |                                      |          |            |         | 1       |                           |
|                |  |   |                                      |          |            |         | Ē       |                           |
|                |  |   |                                      |          |            |         | E       |                           |
|                |  |   |                                      |          |            |         | 3       |                           |
|                |  |   |                                      |          |            |         | 3       |                           |
|                |  |   |                                      |          |            |         | 1       |                           |
|                |  |   |                                      |          |            |         | ÷       |                           |
|                |  |   |                                      |          |            |         | 1       |                           |
|                |  |   |                                      |          |            |         | )+ 10mm |                           |
|                |  |   |                                      |          |            |         | m       |                           |
| IP 55          | Protection against penetration o   | f dust. (dust protected) Protection against penetrat  | ion of water jets.                   |          |            |         |         |                           |
|                | Lightings of Protection Class III<br>Luminaire in which protection ag<br>genrated. | ainst electric shock relies on supply at safety extra | n-low voltage (SELV) and in whic     | ch volta | iges       | higher  | than t  | hose of SELV are not      |
| ₩              | Because of the complex manufa  | cturing process of the LED the above shown data       | are just a statistical size, which i | s not fo | orcec      | I to be | the re  | alistic data of every LEI |
| ▲              |  |   | a service technician appointed b     |          |            |         |         | le quelified person       |

page 2 of 2