

PHILIPS

Lighting



MSD Platinum (Touring/ Stage)

MSD Platinum 11 R 1CT/8

The MSD Platinum lamps open up new levels of creative freedom in entertainment lighting, with powerful, compact and brilliantly intense light. Their compact, lightweight design provides the freedom to create smaller, lighter luminaires – for use at any location on stage. And their short arc, high color temperature and innovative reflector produce a sparkling, high beam intensity for outstanding color reproduction. They also offer long and reliable lifetime, high efficacy and fast replacement times. It all adds up to an intensely exciting creative experience.

Product data

General Information	
Cap-Base	- [-]
Operating Position	UNIVERSAL [Any or Universal (U)]
Main Application	Stage/Touring
Life to 50% Failures (Nom)	2000 h
System Description	Reflector-E20.9

Light Technical	
Color Code	2
Luminous Flux (Nom)	12000 lm
Chromaticity Coordinate X (Nom)	0.300
Chromaticity Coordinate Y (Nom)	0.305
Correlated Color Temperature (Nom)	7800 K
Color Rendering Index (Nom)	-

Operating and Electrical	
Power (Rated) (Nom)	250 W
Voltage (Max)	80 V

Voltage (Min)	55 V
---------------	------

Controls and Dimming	
Dimmable	Yes

Mechanical and Housing	
Cap-Base Information	-

Luminaire Design Requirements	
Pinch Temperature (Max)	350 °C

Product Data	
Full product code	871869653976700
Order product name	MSD Platinum 11 R 1CT/8
EAN/UPC - Product	8718696539767
Order code	928191705314
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	8


MSD Platinum (Touring/Stage)

Material Nr. (12NC)	928191705314
Net Weight (Piece)	85.000 g

Warnings and Safety

- A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.


Dimensional drawing




MSD Platinum 11 R

Product	D (max)	T (max)	O	C (max)
MSD Platinum 11 R 1CT/8	51.5 mm	10 mm	0.95 mm	53 mm

Photometric data



MSD



MSD

