



MSR Gold™ MiniFastFit (Touring/Stage)

MSR Gold™ 1000 MiniFastFit 1CT/4

Thanks to the specially designed lamp base, the MSR Gold™ MiniFastFit takes just seconds to replace, to help ensure non-stop clubbing entertainment. In addition, the innovative gold plated pins ensure excellent current transfer to prolong lamp and lamp holder lifetimes and thereby reduce lamp replacement costs. Easy handling and small compact fixture designs are allowed by the lamps compact size, while the very short arc provides a high perceived brightness and high beam intensity.

Product data

General Information		Lamp Current (Nom)		11.4 A	
Cap-Base	PGJX36 [PGJX36]	Ignition Supply Voltage (Min)	198 V		
Operating Position	UNIVERSAL [Any or Universal (U)]	Controls and Dimming			
Main Application	Entertainment	Dimmable	Yes		
Life to 50% Failures (Nom)	900 h	Mechanical and Housing			
System Description	MiniFastFit	Cap-Base Information	PGJX36		
Light Technical		Luminaire Design Requirements			
Color Code	- [Not Specified]	Bulb Temperature (Max)	950 °C		
Luminous Flux (Min)	74000 lm	Pinch Temperature (Max)	500 °C		
Luminous Flux (Nom)	82000 lm	Product Data			
Chromaticity Coordinate X (Nom)	0.321	Full product code	871829178508800		
Chromaticity Coordinate Y (Nom)	0.330	Order product name	MSR Gold™ 1000 MiniFastFit 1CT/4		
Correlated Color Temperature (Nom)	6000 K	EAN/UPC - Product	8718291785088		
Luminous Efficacy (rated) (Nom)	82 lm/W	Order code	928171405115		
Color Rendering Index (Nom)	80	Numerator - Quantity Per Pack	1		
Operating and Electrical					
Power (Rated) (Nom)	1000.0 W				


MSR Gold™ MiniFastFit (Touring/Stage)

Numerator - Packs per outer box	4
Material Nr. (12NC)	928171405115
Net Weight (Piece)	0.055 kg

Warnings and Safety

- A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.

Dimensional drawing



Product	D (max)	O	L (min)	L (max)	L	C (max)	F (max)	F	F (min)
MSR Gold™	26 mm	5.5	55 mm	57 mm	56	112 mm	36.5	36	35.3
1000		mm			mm		mm	mm	mm
MiniFastFit									
1CT/4									

MSR GOLD 1000 MiniFastFit

