

# Ignitors for high intensity discharge lamps

## Parallel ignitors

- Compact dimensions
- Operating with 250, 400 and 2000W HPI lamp
- To be used only with parallel ballasts
- Available with screw and click mounting
- Screw terminal blocks



Product name	Ordering code	Power [W]	Lamps	Mains voltage [V]	Mains frequency [Hz]	Ignition voltage [kV]		Tc [°C]	Ta [°C]	Cable length [m]	Housing	Dimensions [mm]			
						min	max					A1	A2	B1	C1
SI 51 220-240V 50/60Hz	1010 111 10846	250 ... 400	HPI	220-240	50/60	0.58	0.75	85	-20 ... +75	1500*	Plastic click	84	77	40	35
<b>SI 51-S 220-240V 50/60Hz</b>	<b>1010 111 10946</b>	<b>250 ... 400</b>	<b>HPI</b>	<b>220-240</b>	<b>50/60</b>	<b>0.58</b>	<b>0.75</b>	<b>85</b>	<b>-20 ... +75</b>	<b>1500*</b>	<b>Plastic screw</b>	<b>88</b>	<b>78</b>	<b>40</b>	<b>35</b>
SI 52 220-240V 50/60Hz	1010 111 11246	1000 ... 2000	HPI	220-240	50/60	0.58	0.75	85	-20 ... +75	350*	Plastic click	84	77	40	35
SI 52-S 220-240V 50/60Hz	1010 111 11346	1000 ... 2000	HPI	220-240	50/60	0.58	0.75	85	-20 ... +75	350*	Plastic screw	88	78	40	35
SI 54 380-440V 50/60Hz	1010 111 11646	2000	HPI	380-440	50/60	0.90	1.50	75	-20 ... +65	1200*	Plastic click	113	106	40	35
SI 54-S 380-440V 50/60Hz	1010 111 11946	2000	HPI	380-440	50/60	0.90	1.50	75	-20 ... +65	1200*	Plastic screw	117	106	40	35

\*with typical cable of 100pF per meter

