

# IMPERIO

## AMPLIFIER:

- 240W Class RMS D Amplifier Module
- Switching Power Design
- LED Power / Signal / Clip Indicator
- 24-bit DSP Selectable Configurations
- Input: 1x 3pin XLR / powerCON (NAC3FCA)
- Output: 1x 3pin XLR powerCON (NAC3FCB)
- Volume: Selectable Input Sensitivity Dial
- Power Input: 100-240V ~ 50/60Hz



## SPEAKER:

- 2x 4.75" Neodymium Woofers with 1-inch voice coil
- 6x 1.75" IDVAT HF drivers  
(Inverted Dome Vertical Array Technology)
- Type: 2-Way Active Closed Design
- Frequency Response: 150Hz – 20KHz
- Max Output SPL: 117dB  
(single box measured on Axis @1m)
- Selectable Input Sensitivity:  
-3dB, 0dB, 3dB, 6dB
- Cabinet: ABS Plastic
- Grill: 1.0mm steel
- Splay Angles: 0, 4, 8, & 12-degrees
- Integrated Rigging: Yes
- Dispersion Angle: 90-degree x 15-degree
- Dimensions (LxWxH):  
7.3"x8.8"x12.8" / 184.8x224x324mm
- Weight: 14 lbs. / 6.3 kg.



IDVAT  
HF DRIVERS

