

SONIC XS

COD.: 2999



Stativi non inclusi.
Stand not included

350W
Active



DATI TECNICI		TECHNICAL DATA	
Passivo o Attivo:	Attivo	Passive Or Active	Active
Potenza	350 W RMS	Cabinet Power Handling	350 W RMS 350
Ampl. Bassi	Potenza 250 W RMS	Low Frequency Amplifier	Power Output 250W RMS
Amplificatore Satelliti	2 x 50 W RMS @ 4 ohm	Satellite Amplifier Output	2 x 50 W RMS @ 4 Ohm
Max SPL	118 dB	Max. Sound Pressure Level	118 dB
Sensibilità (1W/1m)	94 dB	Sensitivity (1W/1m)	94 dB
Frequenza lavoro	30 Hz - 250 Hz	Frequency Response	30 Hz-250 Hz
Rapporto (S/NR)	90 dB	Signal To Noise Ratio (S/NR)	90 dB
Distorsione sonora	<0.1 %	Third Harmonic Distortion	<0.1%
CrossOver	200 Hz	Crossover Frequency	200 Hz
Ingressi principali	XLR simmetrico	Main Line Level Input	Balanced XLR: yes
Ingresso Aux	RCA	Aux Line Level Input	Unbalanced Line Level
Ingresso Mic	XLR 3poli / Jack 6,35	Speakon Connection	Wiring Configuration .+1/-1
Cavo Satellite	Speakon, +1 / -1	Mains Power	IEC C14 Inlet
Mic Eq	2 Band	Mic EQ	2 band
Banda bassa frequenza	+/-10 dB @ 100 Hz	Low Frequency Band	./-10 dB @ 100 Hz
Banda alta frequenza	+/-10 dB @ 10 kHz	High Frequency Band	./-10 dB @ 10 kHz
Peso	44,5 kg	Weight	44,5 kg
SUBWOOFER		SPECIFICATIONS SUBWOOFER	
Frequenza di lavoro	30 Hz - 250 Hz	Frequency Response	30 Hz - 250 Hz
Impedenza	4 Ohm	Nominal Impedance	4 Ohm
Woofers	12" (4 Ohm)	Woofers	12" (4 Ohm)
Dimensioni (LxAxP)	380 x 528 x 450 mm	Dimensions (LxHxW)	380 x 528 x 450 mm
Peso	31,5 kg	Weight	31,5 kg
XS SATELLITE		SPECIFICATIONS XS SAT	
Passivo, 6,25" woofer(4 Ohm) + 1" Tweeter		Passive, 6,25" (4 Ohm) + 1" Top Speaker	
Impedenza	4 Ohm	Nominal Impedance	4 Ohm
Potenza	50 W RMS @ 4 Ohms	Power Handling	50 W RMS @ 4 Ohms
Max SPL	107 dB	Max. Sound Pressure Level	107 dB
Sensibilità (1W/1m)	90 dB	Sensitivity (1W/1m)	90 dB
Frequenza lavoro	150 Hz - 20 KHz	Frequency Response	150 Hz - 20 kHz
Connettore di ingresso	Speakon	Speaker Level Input	Speakon: yes (x1)
Cavo Speakon	+1 / -1	Wiring Configuration	./+1/-1
Dimensioni (LxAxP)	210 x 220 x 350 mm	Dimensions (LxHxW)	210 x 220 x 350 mm
Peso	6,5 kg	Weight	6,5 kg

ACCESSORI /	ACCESSORIES
Code 12720	Kit stativo Nero
Code 12721	Kit stativo Grigio
CODE 20040	Cavo speakon m/f 5mt
CODE 20041	Cavo speakon m/f 10mt
CODE 20042	Cavo speakon m/f 15mt
CODE 20043	Cavo speakon m/f 20mt