



ANTARI M-1 Mobile Fogger

Small rechargeable smoke machine

- Portable smoke machine
- Can be taken everywhere
- Smoke output approx. 2.5 m

No. 51701925

Technical specifications:

Power supply:	12 V DC
Power consumption:	75 W
Output volume:	300 cft/min. (approx. 8.5 m ³ /min.)
Smoke output:	approx. 2.5 m
Tank capacity:	0.11 l
Dimensions (WxDxH):	227 x 66 x 81 mm
Weight:	2.7 kg



NEW DMX WDMX

ANTARI M-4 Stage Fogger

High-performance fog machine with digital wireless control system

- Powerful 1500 W
- Vertical and horizontal fog output possible
- New housing design allows upward and downward fog output
- M10 threads for suspended installation
- Intelligent wireless control system W-1 with 50 m range
- Control via integrated DMX interface or control module with LCD screen

No. 51701904

Technical specifications:

Power supply:	230 V AC 50 Hz~
Power consumption:	1500 W
Tank capacity:	2.4 l
Output distance:	5 m high, 1 m wide
Warm-up time:	5 min.
Fluid consumption:	6 ml/min.
Dimensions (LxWxH):	345 x 193 x 386 mm
Weight:	11 kg



DMX



ANTARI M-5 Stage Fogger with Controller

High-performance fog machine with DMX interface

- Powerful 1500 W fogger for stage and touring applications
- Optional wireless controller M-30
- Control module with LCD

No. 51701905

Technical specifications:

Power supply:	230 V AC 50 Hz~
Power consumption:	1500 W
Tank capacity:	10 l
Warm-up time:	approx. 8 min.
Fluid consumption:	approx. 6 ml./l
Output volume:	20000 cft/min. (approx. 570 m ³ /min.)
Dimensions (LxWxH):	659 x 319 x 270 mm
Weight:	18 kg



NEW DMX WDMX RGBA

ANTARI M-7E Stage Fogger with RGBA-LEDs

High-performance fog machine with digital wireless control system and wireless DMX receiver

- Powerful 1500 W
- Colorful columns thanks to RGBA LED illumination at output nozzle
- 10 color macros and 15 chases selectable
- Vertical and horizontal fog output possible
- M10 threads for suspended installation
- Intelligent wireless control system W-2 with 50 m range
- Control via integrated DMX interface or control module with LCD screen



No. 51701907

Technical specifications:

Power supply:	230 V AC 50 Hz~
Power consumption:	1500 W
Tank capacity:	2.4 l
Output distance:	5 m high, 1 m wide
Warm-up time:	5 min.
Max. output:	8 s burst
Fluid consumption:	150 ml/min.
Number of LEDs:	22 (5 x R, 6 x G, 6 x B, 5 x A)
LED type:	3 W
Dimensions (LxWxH):	345 x 193 x 386 mm
Weight:	11 kg

DMX



ANTARI M-8 Stage Fogger with Controller

High-performance fog machine with DMX interface

- Powerful 1800 W fogger for stage and touring applications
- Optional wireless controller M-31
- Control module with LCD

No. 51701908

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	1800 W
Tank capacity:	10 l
Warm-up time:	approx. 8 min.
Fluid consumption:	approx. 7 min./l
Output volume:	approx. 70 m ³ /min.
DMX512 connection:	5-pin and 3-pin XLR
Dimensions (LxWxH):	668 x 319 x 270 mm
Weight:	15 kg