



KEY FEATURES

- Revitalize your 300/500/650 W Fresnel fixtures thanks to ReLite: your true retrofit LED relamping option
- Flicker-free ideal for TV/Broadcast installations
- Excellent white light quality with CRI>90
- Smooth dimming from 30/35 to 100% from traditional triac AC or igbt dimmers
- No color-shift with dimming
- Huge power savings (reduce your power consumption by over 90%) with almost no heat generated
- No heat on your subject



SPECIFICATIONS

- Fixed white CCT at 3200 K or 5600 K
- Full-range dimming on your existing AC Dimmers
- Flicker-free (dimming with costant current)
- Thermal protection
- Instantly upgrade an existing Arri, ADB or De Sisti (and more)

ELECTRICAL SPECIFICATIONS AND CONNECTIONS

- Power supply: 90 -240 Vac, 50-60 Hz
- Max power consumption: 0.31 A at 230V, $\text{Cos}\phi$ 0.98
- Pin connectors: GX9.5, GY9.5, G22

LIGHT SOURCE

- Modular 70 W COB LED
- LEDs life: 20.000 hours at 70% lumen intensity maintenance

PHYSICAL SIZE

- Depth: 73.7 mm (2.90 in)
- Width: 76.5 mm (3.01 in)
- Height: 77 mm (3.03 in)
- Height with connectors: 96 mm (3.78 in)
- Weight: 0.3 Kg (0.66 lbs)



DRAWING SIZE

