Product datasheet

Article no.: 840012

Flexible LED stripe, 5050-72-12V-2700K-3m, IP 33



Technical Data

Dimensions & Weight Length 3000 mm Width 10 mm Height 3 mm Product weight 116 g Cutting possibility (each) 14 mm / 1 LED



Electrical Characteristics

Power / power consumption	36,00 W / 36,00 W
Input voltage	12V DC
Input current	
Connection possibility	wire with open ends
Protection class I, II, III	III

Light Technical Data

Colour Designation	warmwhite
Colour temperature	2700 K
Luminous Flux	1800 lm
Beam angle	120°
LED type	SMD 5050
LED quantity	216

Absolute maximum ratings

The LED will get damaged and the lifetime will decrease when you overrun absolute maximum ratings.

Working temperature	-15°C - +50°C
Storage temperature	-10°C - +60°C
IP - Code	IP 33



Product datasheet

Article no.: 840012

Flexible LED stripe, 5050-72-12V-2700K-3m, IP 33



General product data

Environmental Characteristics

Energy Label	В
Energy consumption	40 kWh/1000h

Lifespan

Lamp life time	30000 h
Luminous flux end of lifetime	0,70
Number of switching cycles	100000

Instructions for mounting and safety

Don't run the stripe when it is on the role.

Please take care during installing for the correct polarity (V+, V-) and do also use the right power supplies with the following safety measures: SELV (Safety Extra Low Voltage), overload protection and short-circuit protection.

Variable of the LED state of the control of the con

You can cut the LED stripe with a cutter at the marked cutting points on the stripe. An extension is not possible.

Mounting on an aluminum profile is recommended in order to optimize the heat dissipation.

Be careful when you install the LED stripe on conducting surfaces, because the solder contact can cause a short circuit.

Avoid buckling the stripe because the PCB board can be damaged.



ı	D	22
	_	ູວຸວ

 $\label{eq:protection} Protection \ against \ penetration \ of \ foreign \ objects > 2.5 \ mm. \ Protection \ against \ penetration \ of \ sprinkling \ water.$



Lightings of Protection Class I

Luminaire in which protection against electric shock relies on supply at safety extra-low voltage (SELV) and in which voltages higher than those of SELV are not genrated.



Lamps and transformers for installation in furniture or for attachment to the furniture whose flammability is unknown.



Because of the complex manufacturing process of the LED the above shown data are just a statistical size, which is not forced to be the realistic data of every LED.



The light source of this luminaire may only be replaced by the manufacturer or by a service technician appointed by him or by a comparable qualified person