

IP65

CE, RoHS

- IP65
- 220-240Vac 50/60Hz
- 100W
- Cree LED
- 10320 lm (4000 K)
10155 lm (3000 K)
-
- 110°
- Cable 50cm
- Grey / Black
- Aluminium, temp. glass
- 35°C
+55°C
- 2.4 Kg
- 50000 hr (L80B20)



CRONO 100
cod. AR10100-WW

Temp. Col. 3000K
Warm White

CRONO 100
cod. AR10100-NW

Temp. Col. 4000K
Natural White

UGR Trav.
≤24

UGR Long.
≤28


CRI
≥ 80

LED
140 lm/W

Questo dispositivo è
munito di lampade
a LED integrate.

A+
A+
A

LED



CRONO 100

The wide range of Crono floodlight from 10 to 200 Watt is suitable to light up architectural details as well as homogeneous wall washer for facades and vertical surfaces, also suitable for parking lots, parks, gardens and monuments. The Crono series is equipped with 100-400 Lux ambient light sensor with hysteresis +/- 50 Lux and sampling every minute for automatic on/off function.

The SMD 230Vac LED module have a overheating protection system and high efficiency driver >PF 0.95 with a protection against electric discharges: Line-Line > 2KV / Line-GND > 4KV

Code	Input Volt	Color Temperature	Watt	PFC	Lumen	CRI	LED Chip	Beam Angle	Body Material	Front Material	Insulation Class	IP	IK
AR10100-WW	220-240Vac	3000K	100W	90	10155 lm	Ra>80	Cree	110°	Aluminium	Temp. Glass	I	IP65	08
AR10100-NW	220-240Vac	4000K	100W	90	10320 lm	Ra>80	Cree	110°	Aluminium	Temp. Glass	I	IP65	08

