



19"

OMNITRONIC PPA PA amplifier

PA power amplifier

- 1 Line In / 1 Line Out
- 4-16 Ohms output for connecting a passive speaker-system
- Load detection and power control

No. 80709810.....PAP-350
 No. 80709820.....PAP-650
 No. 80709830.....PAP-1000

Technical specifications:

Device:	PAP-350	PAP-650	PAP-1000
Power supply:	230 V AC, 50 Hz ~	230 V AC, 50 Hz ~	230 V AC, 50 Hz ~
Power consumption:			2000 W
Output power:	350 W RMS	650 W RMS	1000 W RMS
Output current:	5 A/ 70 V, 3.5 A/ 100 V	10 A/ 70 V, 6.5 A/ 100 V	5 A/ 70 V, 3.5 A/ 100 V
Speaker outputs:	70 V, 100 V or 4-16 ohms	70 V, 100 V or 4-16 ohms	70 V, 100 V or 4-16 ohms
Input connectors:	XLR, 6.3 mm jack mounting socket	XLR, 6.3 mm jack mounting socket	XLR, 6.3 mm jack mounting socket
Output connectors:	XLR, 6.3 mm jack mounting socket	XLR, 6.3 mm jack mounting socket, screw connectors	XLR, 6.3 mm jack mounting socket, screw connectors
Line input:	300 mV, 10 kohms	300 mV, 10 kohms	300 mV, 10 kohms
Frequency range:	80 Hz - 16 kHz	80 Hz - 16 kHz	80 Hz - 16 kHz
Distortion:	0.5 %/ 1 kHz	0.5 %/ 1 kHz	0.5 %/ 1 kHz
S/N ratio (line):	90 dB	90 dB	90 dB
Protection:	Overheat, overload, short-circuit, DC, softstart	Overheat, overload, short-circuit, DC, softstart	Overheat, overload, short-circuit, DC, softstart
Indicators:	Power, fault, clip, signal	Power, fault, clip, signal	Power, fault, clip, signal
Dimensions:	483 x 385 x 92 mm	483 x 385 x 92 mm	483 x 385 x 138 mm
	Rack installation with 2 U	Rack installation with 2 U	Rack installation with 3 U
Weight:	16 kg	18 kg	24 kg



19"

SD^{HC}

MP3

USB

OMNITRONIC EIO6-350 PA mixing amplifier

PA mixing amplifier with CD receiver

- 6 PA zone outputs (100 V), independently switchable
- Amplifier output power: 1 x 350 W RMS
- Master PA output (70 V and 100 V)
- FM/AM tuner with 24 memory places and station finding
- SD card slot and USB input
- Front aux input (3.5 mm jack)
- 3 microphone inputs (6.3 mm jack, unbal.) with separate level controls
- 3 line inputs (stereo RCA) with separate level controls, 1 line output (stereo RCA)

No. 80709869

Technical specifications:

Power supply:	230 V AC, 50 Hz ~
Power consumption:	700 W
Output power:	350 W RMS
Output type:	70 V, 100 V or 4-16 ohms
Mic inputs:	5 mV, 600 ohms
Line inputs:	300 mV, 10 kohms
Speaker connectors:	Screw connectors, terminal block
Frequency range:	80 Hz - 16 kHz
Distortion:	0.5 % (1 kHz)
S/N ratio:	85 dB (line), 75 dB (mic)
Tuner channel:	FM 87 - 108 Hz
AM 522 - 1,161 Hz	
Tuner step pace:	FM 50 kHz
AM 9 kHz	
Available disc:	CD/-R/-RW (12 cm)
Available storage media:	USB devices and SD(HC) cards up to 32 GB
File system:	FAT32
Playback format:	WAV, WMA, MP3
Aux input:	3.5 mm stereo jack
Dimensions:	483 x 385 x 92 mm
Weight:	14 kg