JUNGSRAM

Innovation is our heritage EST. 1896





Discharge - Single Ended Hot Restrike CSR 2500/SE/HR/UV-C 93106225

Product information

Compact, single ended metal halide hot restrike lamps for a variety of applications requiring high luminance, reliability and excellent colour characteristics. Excellent colour rendering, Ra>90, and high CCT 5600-6000 K with superior colour stability- Universal burn position with hot restrike capability- High efficiency with excellent lumen maintenance

Application areas



Film and Broadcast



Product data

Product Code	93106225
Light Center Length [mm]	127
Bulb Shape	Globe
Bulb Finish	Clear
Bulb Diameter [mm]	60
Maximum Overall Length [mm]	240
Arc Gap	14
Net weight per piece [g]	640
Gross weight per piece [g]	727
Operating position	U - Universal
Brand	Tungsram
Cap/Base	G38

Performance data

Colour Code	956
Rated Lumens [lm]	220000
Weighted energy consumption [kWh/1000h]	2750.0
Nominal chromaticity coordinate X	0.33
Nominal chromaticity coordinate Y	0.325
Nominal correlated colour temperature (CCT) [K]] 5600	
Nominal lumens [lm]	220000
Colour Rendering Index (CRI) [Ra]	90

Electrical data

Rated power [W]	2500.0
Lamp Current [A]	21.7
Dimming Capability	No
Ballast Required	Yes
Nominal power [W]	2500
Nominal lamp voltage [V]	115

Logistic data

DUN Code	15994100020711
EAN Code	5994100020714
Pack Quantity	6
Inner pack type	BOX
Outer pack type	OUTER BOX
Layer quantity	36 EUR, 66 UK
Layer quantity EUR	36
Layer quantity UK	66
Pallet quantity EUR (PC)	108
Pallet quantity UK (PC)	132
Outer case size	385 x 280 x 346 (mm)
Product status	Available

Downloads & Links

Go to the catalog site (HTTP) Entertainment Solution Spectrum Catalogue (PDF) Lighting design tools & calculators (HTTP) High-res images / Technical drawings (HTTP)

TUNGSRAM

Disclaimer

Special Purpose Lamp, Not suited for household illumination



We in Tungsram Operations Kft. are constantly developing and improving our products. For this reason, all product descriptions in this catalogue are intended as a general guide, and we may change specifications from time to time in the interest of product development, without prior notification or public announcement. All descriptions in this publication present only general particulars of the goods to which they refer and shall not form part of any contract. Data in this guide has been obtained in controlled experimental conditions. However, Tungsram cannot accept any liability arising from the reliance on such data to the extent permitted by law.