

HMI DIGITAL 400 W

HMI brand DIGITAL | Lampade ad alogenuri metallici, attacco singolo



Aree applicative

- Studio
- Stage
- TV

Vantaggi prodotto

- Suited for both analog and digital film production
- Robust stems, resulting in less breakage during transport
- Round moly-foil construction that evenly distributes heat and current extends for lamp longevity (6,000-18,000 W)
- Splash-proof carrying case is re-usable and allows lamps to be transported safely (6,000-18,000 W)

Caratteristiche prodotto

- High CRI of >90
- UV-Stop (UVS)
- Color temperature of 6,000 K (daylight)
- Extremely bright light of up to 100 lumens/watt
- Capacità di riaccensione a caldo

Scheda prodotto

Dati tecnici

Dati elettrici

Potenza nominale	400,00 W
Tensione nominale	75,0 V
Corrente nominale	5,3 A

Dati fotometrici

Flusso luminoso nominale	32500 lm
Temperatura di colore	6700 K
Indice di resa cromatica Ra	90

Dimensioni e peso

Diametro	23,0 mm
Lunghezza	110,0 mm

Durata

Durata	650 h
--------	-------

Dati di prodotto aggiuntivi

Attacco (denominazione da norma)	GZY9.5
----------------------------------	--------

Environmental information

Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)	
Date of Declaration	01-11-2022
Primary Article Identifier	4052899984127
Candidate List Substance 1	No declarable substances contained
Declaration No. in SCIP database	No declarable substances contained

Scheda prodotto

Informazione sulla sicurezza

Because of their high luminance, UV radiation and high internal pressure during operation, HMI lamps may only be operated in enclosed lamp casings specially constructed for the purpose. Mercury is released if the lamp breaks. Special safety precautions must be taken. Information on safety and handling is available on request or can be found in the leaflet included with the lamp or in the operating instructions.

Dati logistici

Codice prodotto	Descrizione del prodotto	Unità di imballo (Pezzi/unità)	Dimensioni (lunghezza x profondità x altezza)	Volume	Peso lordo
4052899984127	HMI DIGITAL 400 W	Astuccio 1	46 mm x 46 mm x 143 mm	0.30 dm ³	54.00 g
4052899984165	HMI DIGITAL 400 W	Cartone di spedizione 10	245 mm x 105 mm x 165 mm	4.24 dm ³	612.00 g

1) codice prodotto indicato descrive la minore quantità che può essere ordinata. Una unità di spedizione può contenere uno o più di un singolo prodotto. Quando si inserisce un ordine, per la quantità inserire una o più unità di spedizione.

Clausola

Con riserva di modifiche senza preavviso. Salvo errori o omissioni. Assicurarsi sempre di utilizzare la versione più recente.