

ARRI 300 PLUS



<u>Part no.</u>	<u>Description</u>
LO.79200.B	manual

Accessories

L2.79170.0	Four Leaf Barndoor
L2.79190.0	Diffuser Frame
L2.79180.0	Variable Snoot
L2.79160.M	Scrim Set

Lamps

64673 OSRAM	300W 230V GY9,5 CP/81 3100°K 200 hours (suggested)
64662 OSRAM	300W 230V GY9,5 M/38 2900°K 2000 hours
6872P PHILIPS	300W 230V GY9,5 CP/81 3200°K 150 hours (suggested)
6874P PHILIPS	300W 230V GY9,5 M/38 2950°K 2000 hours

Specifications

Weight	1.5 Kg
Lens Diameter	80 mm
Reflector	Spherical specular high purity aluminium
Lampholder	GY9,5
Packed Size	170 H x 150 W x 140 L mm
Protection Class	IP 23
Certification	NRTL-US-C, CE, TUV GC, CB

Photometric Data with Lamp CP/81*

Throw (m):	1	2	3
Spot:16°			
Output (lux)	13500	3375	1500
Flood:55°			
Output (lux)	2790	698	310

* 1000 lux gives correct exposure for 200ASA film with aperture f4 at 24 fps

