

ARRI 650 PLUS



<u>Part no.</u>	<u>Description</u>
LO.79400.B	manual
LO.79400.I	pole operated

Accessories

L2.79470.0	Four Leaf Barndoor
L2.79480.0	Variable Snoot
L2.79490.0	Diffuser Frame
L2.79460.M	Scrim Set
LS.428-2.5	Operating pole 0.95m - 2.5m
LS.428-40	Operating pole 1.40m - 4.0m



Lamps

6638P PHILIPS	650W 230V GY9,5 CP/89 3200°K 180 hours (suggested)
6823P PHILIPS	650W 230V GY9,5 T/27 3050°K 600 hours
64718 OSRAM	650W 230V GY9,5 T/27 3000°K 400 hours

Specifications

Weight	2.7 Kg
Weight p.o.	5 Kg
Lens Diameter	112 mm
Reflector	Spherical specular high purity aluminium
Lampholder	GY9,5
Packed Size	200 H x 180 W x 170 L mm
Packed Size p.o.	190H x 180 W x 230 L mm
Protection Class	IP 23
Certification	NRTL-US-C, CE, TUV GC, CB

Photometric Data with Lamp CP/89*

Throw (m):	2	3	4
Spot:12°			
Output (lux)	15975	7100	3995
Flood:55°			
Output (lux)	2700	1200	675

* 1000 lux gives correct exposure for 200ASA film with aperture f4 at 24 fps

