

# ARRI 650 PLUS



## Codice

LO.79400.B  
LO.79400.I

## Descrizione

manuale  
pole operated

## Accessori

L2.79470.0	Paraluce a 4 alette
L2.79480.0	Snoot Variabile
L2.79490.0	Diffusore
L2.79460.M	Set diffusore
LS.428-2.5	Operating pole 0.95m - 2.5m
LS.428-40	Operating pole 1.40m - 4.0m

## Lampade

6638P PHILIPS	650W 230V GY9,5 CP/89 3200°K 180 ore (consigliato)
6823P PHILIPS	650W 230V GY9,5 T/27 3050°K 600 ore
64718 OSRAM	650W 230V GY9,5 T/27 3000°K 400 ore

## Specifiche

Peso	2.7 Kg
Peso p.o.	5 Kg
Diametro lenti	112 mm
Riflettore	in alluminio, sferico con alta purezza speculare
Portalamпада	GY9,5
Dimensioni	200 H x 180 W x 170 L mm
Dimensioni p.o.	190H x 180 W x 230 L mm
Classe di protez.	IP 23
Certificazioni	NRTL-US-C, CE, TUV GC, CB

## Dati fotometrici con lampada CP/89\*

Distanza (m):	2	3	4
Stretto:12°			
Uscita (lux)	15975	7100	3995
Largo:55°			
Uscita (lux)	2700	1200	675

\* 1000 lux danno un'esposizione corretta per 200ASA film con apertura f4 a 24 fps

