PHILIPS Lighting



Halogen non-reflector

14623 95W G6.35 17V 1CT/10X10F

Halogen non-reflector lamps offer high-quality light and are easy to install, replace and operate. All halogen non-reflector lamps incorporate a distortion-free quartz bulb and a precise positioning of the mounted filament. These ensure optimal beam performance and consistent, high light output. A wide range of wattages is available for a broad variety of applications, including projection systems. In addition you get all the proven advantages of halogen technology such as a full spectrum and a color rendering index (CRI) of 100 – the same as natural light and the best that it can be. Halogen lamps also create a comfortable warm white light, and they maintain their lumen output, with almost no reduction, throughout their lifetime.

Product data

General Information							
Cap-Base	G6.35 [G6.35]						
Philips Code	14623						
ANSI Code	-						
LIF Code	-						
Operating Position	S90 [Standing +/-90D or Base Down (BDH)]						
Main Application	Projection						
Life to 50% Failures (Nom)	2000 h						
Light Technical							
Luminous Flux (Rated) (Nom)	2150 lm						
Correlated Color Temperature (Nom)	3050 K						
Color Rendering Index (Nom)	-						
Operating and Electrical							
Power (Rated) (Nom)	95 W						


Voltage (Nom)	17 V					
Mechanical and Housing						
Bulb Material	Quartz-UV Open					
Filament Shape	Flat					
Filament Dimensions WxH	5.24 x 3.13					
Luminaire Design Requirements						
Bulb Temperature (Max)	900 °C					
Pinch Temperature (Max)	350 °C					
Product Data						
Full product code	871150042667350					
Order product name	14623 95W G6.35 17V 1CT/10X10F					
EAN/UPC - Product	8711500426673					
Order code	924049819103					
Numerator - Quantity Per Pack	1					

Prodotti commercializzati da: AMLUX s.r.l. 46042 Castel Goffredo (MN) info@amlux.it - www.amlux.it

Halogen non-reflector

Numerator - Packs per outer box	100			
Material Nr. (12NC)	924049819103			
Net Weight (Piece)	0.004 kg			

Dimensional drawing



Product	D (max)	L (min)	L (max)	L	P (max)	Р	P (min)	C (max)
14623 95W	11.5 mm	31.5 mm	32.25	32	1.05 mm	1 mm	0.95 mm	50 mm
G6.35 17V			mm	mm				
1CT/10X10F								



Prodotti commercializzati da: AMLUX s.r.l. 46042 Castel Goffredo (MN) info@amlux.it - www.amlux.it www.lighting.philips.com 2017, September 24 - data subject to change