



**SixPar 100 code: 1236100111**

**SixPar 100 IP code: 1236100102**

**FEATURES**

- IP65-Rated (IP version)
- 15° Beam 25° Field Angles
- Full RGBAW+UV Color Mixing
- UV Wavelength: 395nm
- (5) Variable Dimming Curve Modes
- No Fans - Silent Operation
- Flicker Free Operation for TV and Film
- RDM (Remote Device Management)

**SOURCE**

- (7) 12W 6-in-1 RGBAW+UV LEDs
- 100,000 Hour Average LED Life

**PHOTOMETRIC DATA**

- 2,880 LUX @ 2m (15°)

**ELECTRICAL / THERMAL**

- AC 110-250V - 50/60Hz
- 89W Max Power Consumption
- From -15°C to 45°C
- UV Wavelength: 395nm

**EFFECTS**

- Strobe: 1-18fps
- Dimming: 0% - 100%
- (5) Variable Dimming Curve Modes

**COLOR**

- Full RGBAW+UV Color Mixing and Color Macros
- Variable Color Temperatures

**CONTROL / CONNECTIONS**

- (4) DMX Channel Modes (6 / 7 / 8 / 12)
- (4) Button Control Panel LCD Menu Display
- 3pin & 5pin DMX powerCON In/Out
- IP DMX In/Out and IP Power In/Out (IP version)

**SIZE / WEIGHT**

- Length: 257mm (IP version)/257mm
- Width: 158mm (IP version)/125mm
- Vertical Height: 243mm (IP version)/243mm
- Weight: 4.3kg (IP version)/3,3kg



**SixPar 200 code: 1236100114**

**Sixpar 200 IP code: 1236100103**

**FEATURES**

- IP65-Rated (IP version)
- 15° Beam 25° Field Angles
- Full RGBAW+UV Color Mixing
- UV Wavelength: 395nm
- (5) Variable Dimming Curve Modes
- No Fans - Silent Operation
- Flicker Free Operation for TV and Film
- RDM (Remote Device Management)

**SOURCE**

- (12) 12W 6-in-1 RGBAW+UV LEDs
- 100,000 Hour Average LED Life

**PHOTOMETRIC DATA**

- 5,600 LUX @ 2m (15°)

**ELECTRICAL / THERMAL**

- AC 110-250V - 50/60Hz
- 150W Max Power Consumption
- From -15°C to 45°C
- UV Wavelength: 395nm

**EFFECTS**

- Strobe: 1-18fps
- Dimming: 0% - 100%
- (5) Variable Dimming Curve Modes

**COLOR**

- Full RGBAW+UV Color Mixing and Color Macros
- Variable Color Temperatures

**CONTROL / CONNECTIONS**

- (4) DMX Channel Modes (6 / 7 / 8 / 12)
- (4) Button Control Panel LCD Menu Display
- IP DMX In/Out and IP Power In/Out (IP version)
- 3pin & 5pin DMX powerCON In/Out

**SIZE / WEIGHT**

- Length: 313mm (IP version)/313 mm
- Width: 157mm (IP version)/ 125 mm
- Vertical Height: 300mm (IP version)/ 300mm
- Weight: 5.7 kg (IP version)/ 3,1kg



**SixPar 300 code: 1236100115**

**SixPar 300IP code: 1236100104**

**FEATURES**

- IP65-Rated (IP version)
- 15° Beam 25° Field Angles
- Full RGBAW+UV Color Mixing
- UV Wavelength: 395nm
- (5) Variable Dimming Curve Modes
- No Fans - Silent Operation
- Flicker Free Operation for TV and Film
- RDM (Remote Device Management)

**SOURCE**

- (18) 12W 6-in-1 RGBAW+UV LEDs
- 100,000 Hour Average LED Life

**PHOTOMETRIC DATA**

- 8,500 LUX @ 2m (15°)

**ELECTRICAL / THERMAL**

- AC 110-250V - 50/60Hz
- 220W Max Power Consumption
- From -15°C to 45°C
- UV Wavelength: 395nm

**EFFECTS**

- Strobe: 1-18fps
- Dimming: 0% - 100%
- (5) Variable Dimming Curve Modes

**COLOR**

- Full RGBAW+UV Color Mixing and Color Macros
- Variable Color Temperatures

**CONTROL / CONNECTIONS**

- (4) DMX Channel Modes (6 / 7 / 8 / 12)
- (4) Button Control Panel LCD Menu Display
- IP DMX In/Out and IP Power In/Out (IP version)
- 3pin & 5pin DMX powerCON In/Out

**SIZE / WEIGHT**

- Length: 365mm (IP version)/365mm
- Width: 157mm (IP version)/125mm
- Vertical Height: 365mm (IP version)/365mm
- Weight: 8.7kg (IP version)/8,1 kg

