



SIXBAR 1000 IP™

The new IP65 rated SIXBAR 1000IP™ features (12) 12W 6-IN-1 RGBAW+UV LEDs, 25° beam angle, pixel control, variable dimming curve modes, strobe and chase effects, a UV wavelength of 395nm, RDM (remote device management) protocol support, IP rated DMX and power in/out connections, LCD menu display with 4 touch button control panel, dual adjustable rigging/floor stand brackets, glare shield and (2) lens filters included, multiple unit power linking, rugged die-cast aluminum exterior, flicker free operation for TV and FILM, 145W max power consumption, and a multi-voltage universal auto switching power supply (110-240v).



FEATURES

- IP65 Rated**
- 12 x 12W 6-in-1 RGBAW+UV LEDs**
- 395nm UV Wavelength**
- 25° Beam Angle**
- Pixel Control**
- Variable Dimming Curves**
- Strobe and Zone Chase Effects**
- RDM (Remote Device Management)**
- Dual Adjustable Rigging/Floor Stand Brackets**
- Multiple Unit Power Linking**
- Rugged Die-Cast Aluminum Exterior**
- Flicker Free Operation for TV and FILM**
- Glare Shield and (2) Filter Lens Included**



Glare Shield and (2) Lens Filters Included

PRODUCT SPECIFICATIONS

SOURCE

(12) 12W 6-in-1 RGBAW+UV LEDs
100,000 Hour Average LED Life*

*LED Life may vary depending on several factors including but not limited to: Environmental Conditions, Power/Voltage, Usage Patterns (On-Off Cycling), Control and Dimming.

PHOTOMETRIC DATA

7,149 LUX 664 FC @3.3' (1m) (25° Full ON)

EFFECTS

Pixel Control
Strobe and Chase Effects
Variable and Selectable Dimming Curves

CONTROL / CONNECTIONS

(8) DMX Channel Modes (6 / 7 / 11 / 13 / 36 / 72 / 75 / 79)
4 Button Touch Control Panel and LCD Menu Display
RDM (Remote Device Management)
IP Rated 5pin DMX In/Out
powerCON TRUE1 Power In/Out

SIZE / WEIGHT (dimensions without Glare Shield)

Length: 33.6" (853mm)
Width: 5.6" (141.4mm)
Vertical Height: 4.7" (120.5mm)
Weight: 19.0 lbs. (8.6 kg)

ELECTRICAL / THERMAL

AC 110-240V - 50/60Hz
145W Max Power Consumption
Multiple Unit Power Linking
5°F to 113°F (-15°C to 45°C)
395nm UV Wavelength

APPROVALS / RATINGS

IP65


INCLUDED ITEMS

powerCON TRUE1 Cable
Glare Shield
(2) Lens Filters




**Omega Bracket
(optional - not included)**

PHOTOMETRIC DATA



	1 m	3.3 ft	2 m	6.6 ft	3 m	9.8 ft	4 m	13.1 ft	5 m	16.4 ft
25° Beam Diameter	0.45	1.5	0.88	2.9	1.33	4.4	1.77	5.8	2.21	7.3
	lux	fc	lux	fc	lux	fc	lux	fc	lux	fc
RED LEDs	1,253	116	542	50	283	26	172	16	119	11
GREEN LEDs	3,267	304	1,416	132	726	67	429	40	275	26
BLUE LEDs	469	44	211	20	108	10	65	6	45	4
WHITE LEDs	2,813	261	1,216	113	621	58	372	35	242	22
AMBER LEDs	1,286	119	532	49	271	25	153	14	101	9
UV LEDs	50	5	24	2	13	1	10	1	7	1
FULL ON	7,149	664	2,910	270	1,481	138	880	82	603	56

DIMENSIONAL DIAGRAMS



OPTIONAL ACCESSORIES

ORDER CODE	ITEM
TRIGGER CLAMP	Heavy Duty Wrap Around Hook Style Clamp
8050000057	Omega Bracket (single)
EWD001	EWDWMX IP Wireless IP65 DMX Transceiver
NEU088	3' (1m) powerCON TRUE1 Power Link Cable
	Additional cable lengths available