



Halogen non-reflector

7787XHP 400W GY6.35 36V 1CT/3X8F

Halogen non-reflector lamps offer high-quality light and are easy to install, replace and operate. All halogen non-reflector lamps incorporate a distortion-free quartz bulb and a precise positioning of the mounted filament. These ensure optimal beam performance and consistent, high light output. A wide range of wattages is available for a broad variety of applications, including projection systems. In addition you get all the proven advantages of halogen technology such as a full spectrum and a color rendering index (CRI) of 100 – the same as natural light and the best that it can be. Halogen lamps also create a comfortable warm white light, and they maintain their lumen output, with almost no reduction, throughout their lifetime.


Product data

General Information		Voltage (Nom)	
Cap-Base	G6.35 [G6.35]		36 V
Philips Code	7787XHP	Mechanical and Housing	
ANSI Code	EVD	Bulb Material	Quartz-UV Open
LIF Code	A1/239	Filament Shape	Flat
Operating Position	S90 [Standing +/-90D or Base Down (BDH)]	Filament Dimensions WxH	9.4x4.7
Main Application	Projection	Luminaire Design Requirements	
Life To 50% Failures (Nom)	50 h	Bulb Temperature (Max)	900 °C
		Pinch Temperature (Max)	400 °C
Light Technical		Product Data	
Luminous Flux (Rated) (Nom)	16000 lm	Full product code	871150050458638
Correlated Color Temperature (Nom)	3250 K	Order product name	7787XHP 400W GY6.35 36V 1CT/3X8F
Color Rendering Index (Nom)	100	EAN/UPC - Product	8711500504586
Operating and Electrical		Order code	924031623306
Power (Rated) (Nom)	400 W	Numerator - Quantity Per Pack	1

Halogen non-reflector

Numerator - Packs per outer box	24
Material Nr. (12NC)	924031623306
Net Weight (Piece)	0.008 kg

Dimensional drawing



Product	D	L	L	L	P	P	P
7787XHP 400W GY6.35 36V 1CT/3X8F	18 mm	35.75 mm	36.25 mm	36 mm	1.05 mm	1 mm	0.95 mm

7787XHP 400W G6.35 36V

