

The high, constant output and consistent color temperature of these single ended halogen lamps ensure attractive, accurately exposed pictures for both film and video. Furthermore, these lamps incorporate the highly innovative P3 technology, developed by Philips. This allows the lamps to be used at higher temperatures, which extends overall lifetime and consistency of their high-quality light output. P3 technology also allows the lamp to be used in any burning position and enables more compact designs of fixtures. In addition, the very wide choice of dimensions and power ratings opens new levels of creative freedom for the luminaire designer.

See full family

Add to ProjectPlanner





















Product Information

General Characteristics		
Philips Code	6873P	•
ANSI Code	FRH	•
LIF Code	CP/82	•
Cap-Base	GY9.5	•
Bulb Finish	Clear	•
Filament Shape	М	•
Operating Position	any	•
Main Application	Entertainment	•
Life to 50% failures	150 hr	•
Light Technical Characteri	stics	
Color Temperature Technical	3200 K	•
Luminous Flux Lamp	13500 Lm	•
Electrical Characteristics		
Watts	500 W	•
Voltage	230 V	•
Dimmable	Yes	

Luminaire Design Requirements


Pinch Temperature	350 (max) C	•
Product Dimensions		
Overall Length C	90 (max) mm	•
Diameter D	18 (max) mm	•
Pin Length K	7.11 (min), 8.6 (max) mm	40
Light Center Length L	46.5 mm	•
Pin Distance R	9.53 mm	•
Filament Dimensions (WxH) [mm]	8x18	•
Filament Height H	18 mm	•
Filament Length W	8 mm	•
Product Data		
Product number	258061	•

6873P 500W •

GY9.5 230V 1CT

+ More info / Hide info

Full product name



Installation diagrams

Rapid Acting HBC Fuse

4 V







GY9.5 + Zoom

GY9.5 + Zoom

+ Zoom