



PAR 36 4515 6.4V **24673**

Product information

PAR lamps provide a robust and flexible design solution for a wide range of applications. Choice of PAR36, PAR46, PAR56 or PAR64

- 3000 K or 4200 K colour temperature
- Choice of beam widths
- Excellent colour rendering
- High efficiency combined with low operating costs
- Robust and reliable
- UV control
- Easy retrofit
- Colour consistent throughout life
- Colour blends with halogen and fluorescent







Product data

Cap/Base	Screw terminal
Bulb Shape	PAR
Bulb Diameter [mm]	114
Maximum Overall Length [mm]	70
Light Center Length [mm]	41.27
Net weight per piece [g]	437
Gross weight per piece [g]	546
Brand	General Electric (GE)

Performance data

Nominal beam angle [°]	15
Nominal center beam candlepower (CBCP) [cd]	55000
Energy efficiency class (EEC)	E
Nominal power [W]	30
Nominal lamp voltage [V]	6

Electrical data

Weighted energy consumption [kWh/1000h]	31.58
Lamp Current [A]	4.69
Coil type	C-6
Dimming Capability	Yes
Ballast Required	Yes





Logistic data

DUN Code	00043168246736
EAN Code	0043168246736
Pack Quantity	12
Layer quantity	240 UK
Layer quantity UK	240
Pallet quantity EUR (PC)	1520
Pallet quantity UK (PC)	1200
Outer case size	310 x 209 x 218 (mm)
Product status	Available

Application areas



Club and Disco

Downloads & Links

Go to the catalog site (HTTP) Entertainment Solution Spectrum Catalogue (PDF) Lighting design tools & calculators (HTTP)

Disclaimer

Special purpose lamp – Stage Studio. Not suitable for household illumination.