




GE
Lighting



PAR 64
Q4559X 28.0V
42552

Product information

PAR lamps provide a robust and flexible design solution for a wide range of applications. Choice of PAR36, PAR46, PAR56 or PAR64

- 3000 K or 4200 K colour temperature
- Choice of beam widths
- Excellent colour rendering
- High efficiency combined with low operating costs
- Robust and reliable
- UV control
- Easy retrofit
- Colour consistent throughout life
- Colour blends with halogen and fluorescent

Application areas



Club and Disco



Product data

Cap/Base	Screw terminal
Bulb Shape	PAR
Bulb Diameter [mm]	203.2
Maximum Overall Length [mm]	95.25
Net weight per piece [g]	938
Gross weight per piece [g]	1119
Brand	General Electric (GE)

Performance data

Nominal beam angle [°]	15
Nominal center beam candlepower (CBCP) [cd]	765000

Electrical data

Nominal power [W]	600
Nominal lamp voltage [V]	28
Lamp Current [A]	21.4
Coil type	CC-6
Ballast Required	Yes

Logistic data

DUN Code	00043168425520
Pack Quantity	12
Layer quantity	72 EUR, 108 UK
Layer quantity EUR	72
Layer quantity UK	108
Pallet quantity EUR (PC)	72
Pallet quantity UK (PC)	108
Outer case size	384 x 354 x 551 (mm)
Product status	Available

Downloads & Links

[Go to the catalog site \(HTTP\)](#)

[Entertainment Solution Spectrum Catalogue \(PDF\)](#)

[Lighting design tools & calculators \(HTTP\)](#)

[High-res images / Technical drawings \(HTTP\)](#)

[Certificate for the Quality Management System of GE Lighting EMEA \(PDF\)](#)

[Certificate for the Environmental Management System of GE Lighting EMEA \(PDF\)](#)

Disclaimer

Special Purpose Lamp, Not suited for household illumination