

MSR

MSR 700/2 1CT/8

The high color rendering index of the single ended MSR series ensures that everyone in the audience can enjoy the true colors of the scenery, the stage props, the players and their costumes — in fact everything that is on stage can be made bright and vivid in daylight quality light. Also, thanks to the single ended lamp concept, the luminaire has optimal light collection and direction possibilities to help ensure brightness on stage exactly where and when it is needed. In addition, the MSR can be used in any burning position for easy set-up and convenience.

Product data

• General Information

Cap-Base G22 [G22]
Operating Position UNIVERSAL [Any or Universal (U)]
Main Application Studio/Disco
Life To 50% Failures (Nom)

System Description Cold Strike

• Light Technical

Color Code 48000 lm Luminous Flux (Min) 55000 lm Luminous Flux (Nom) Chromaticity Coor-302 dinate X (Nom) Chromaticity Coor-320 dinate Y (Nom) Correlated Color 7200 K Temperature (Nom) Luminous Efficacy 78 lm/W (rated) (Nom) Color Rendering Index (Nom)

Operating and Electrical

Power (Rated) 700 W (Nom)

Lamp Current (Nom) 11 A

Ignition Supply 207 V Voltage (Min)

• Controls and Dimming

Dimmable No

• Mechanical and Housing

Cap-Base Information

• Luminaire Design Requirements

Bulb Temperature 700 °C (Max)
Pinch Temperature 350 °C (Max)

• Product Data

872790091638600 Full product code MSR 700/2 1CT/8 Order product name EAN/UPC - Product 8727900916386 Order code 928171505114 Numerator - Quantity Per Pack Numerator - Packs 8 per outer box Material Nr. (12NC) 928171505114 Net Weight (Piece) 0.120 kg




Warnings and Safety

• A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and


remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.

Dimensional drawing




MSR 700/2





Photometric data





© 2016 Philips Lighting Holding B.V. All rights reserved.

Specifications are subject to change without notice. Trademarks are the property of Koninklijke Philips N.V. (Royal Philips) or their respective owners.