

---


## HTI 1200 W/SE XS

HTI | Metal halide lamps, single-ended

---

### Product benefits

- High luminance
- High luminous efficacy and efficiency



**Prodotti commercializzati da:**  
**AMLUX s.r.l.**  
**46042 Castel Goffredo (MN)**  
**[info@amlux.it](mailto:info@amlux.it) - [www.amlux.it](http://www.amlux.it)**

Product datasheet

Technical data


Electrical data

Nominal wattage	1200 W
Nominal voltage	95.0 V
Lamp voltage	100 V
Nominal current	13.8 A
Lamp current	12.7 A

Photometrical data

Luminance	26000 cd/cm <sup>2</sup>
Color temperature	5400 K

Dimensions & weight



Length	135.0 mm
Light center length (LCL)	59.0 mm

Lifespan

Lifespan	750 h
----------	-------

Additional product data

Base (standard designation)	GY22 <sup>1)</sup>
-----------------------------	--------------------

<sup>1)</sup> Special GY22 base. The ignition voltage may be applied only to the thin pin

Capabilities

Burning position	s135 <sup>1)</sup>
------------------	--------------------

<sup>1)</sup> Current strap underneath

Certificates & standards

**Prodotti commercializzati da:**  
**AMLUX s.r.l.**  
**46042 Castel Goffredo (MN)**  
**info@amlux.it - www.amlux.it**

Product datasheet

EEI – Energy Label	B
--------------------	---

Country specific information


Product code	METEL code	SEG-No.	STK-Number	UK Org
4050300371153	OSRHTI1200SE	-	-	-

**Prodotti commercializzati da:**  
**AMLUX s.r.l.**  
**46042 Castel Goffredo (MN)**  
**info@amlux.it - www.amlux.it**

Product datasheet

Safety advice

Because of their high luminance, UV radiation and high internal pressure during operation, HTI lamps may only be operated in enclosed lamp casings specially constructed for the purpose. Appropriate filters must ensure that UV radiation is reduced to an acceptable level. Mercury is released if the lamp breaks. Special safety precautions must be taken. Information on safety and handling is available on request or can be found in the leaflet included with the lamp or in the operating instructions.



Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4050300371153	HTI 1200 W/SE XS	Shipping carton box 1	305 mm x 82 mm x 115 mm	2.88 dm <sup>3</sup>	249.00 g

- The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

**Prodotti commercializzati da:**  
**AMLUX s.r.l.**  
**46042 Castel Goffredo (MN)**  
**info@amlux.it - www.amlux.it**