

MSR Gold™ FastFit

MSR Gold™ 2000 FastFit 1CT/8

All lamps burn out eventually, but when this happens with single ended MSR Gold[™] FastFit, it is replaced in seconds – thanks to the specially designed lamp base and lamp holder. This lamp provides a high beam intensity of pure, white light for a truly illuminating performance, while the goldplated caps provide superior heat protection and prevent premature failure. P3 technology allows use in any position and at higher temperatures, further extending lamp life and consistency of high-quality light output. Also, because the FastFit design is applied to Philips Halogen lamps, switching between lamp technologies can be done quickly and easily. The Philips MSR GoldTM 1200 FastFit can be operated in a lamp wattage range between 800W and 1400W.

Product data

• General Information

Cap-Base Operating Position Main Application Life To 50% Failures (Nom) System Description

PGJX50 [PGJX50] UNIVERSAL [Any or Universal (U)] Entertainment 750 h

• Light Technical

Color Code Luminous Flux (Min)	- [Not Specified] 154000 lm
Luminous Flux	162000 lm
(Nom) Chromaticity Coor-	321
dinate X (Nom) Chromaticity Coor-	332
dinate Y (Nom)	332
Correlated Color Temperature (Nom)	6050 K
Luminous Efficacy	81 lm/W
(rated) (Nom) Color Rendering	91
Index (Nom)	<i>·</i> ··

• Operating and Electrical

Power (Rated)	2000 W
(Nom)	
Lamp Current (Nom)	15.2 A

FastFit

Bulb Temperature 950 °C (Max) Pinch Temperature 500 °C (Max) • Product Data Full product code

Ignition Supply

Voltage (Min)

Dimmable

Controls and Dimming

• Mechanical and Housing

Cap-Base Information PGJX50

Luminaire Design Requirements

198 V

Yes

Order product name EAN/UPC - Product Order code Numerator - Quantity Per Pack Numerator - Packs per outer box Material Nr. (12NC) Net Weight (Piece)

872790091949300 MSR Gold[™] 2000 FastFit 1CT/8 8727900919493 928176905114

928176905114 0.147 kg

1

8

Prodotti commercializzati da: AMLUX s.r.l. 46042 Castel Goffredo (MN) info@amlux.it - www.amlux.it




MSR Gold[™] FastFit

Warnings and Safety

• A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and


Dimensional drawing



MSR Gold™ 1500, 2000(/2), 2500/2

MSR GOLD 2000W FastFit

Product	D	0	L	L	L	С	F
MSR Gold™ 2000 FastFit 1CT/8	34 mm	8.0 mm	66 mm	68 mm	67 mm	134 mm	50 mm





© 2016 Philips Lighting Holding B.V. All rights reserved.

Specifications are subject to change without notice. Trademarks are the property of Koninklijke Philips N.V. (Royal Philips) or their respective owners.

www.philips.com/lighting

Prodotti commercializzati da: AMLUX s.r.l. 46042 Castel Goffredo (MN) info@amlux.it - www.amlux.it

remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.