



Delivery without accessories

HR - ALUMINUM

Information

- for LED lighting with flexible stripes up to 10,8 mm width
- for wall- and floor installation (walkable)
- for damp locations and lighting of indoor and outdoor areas (only suitable with the appropriate IP protection)

Application

- accent lighting, decorative lighting, light-line marking, swimming pools, landscape architecture

mounting (not in range)


- mounting glue or tile adhesive

Ending (not in range) (not in range)

- we recommend silicone glue (DOW CORNING 794, transparent)

Advantages

- designed to meet IP67 waterproof level
- small in size, walkable
- good heat output, easy installation, light in weight, environmentally friendly



HR - ALUMINUM

aluminum

990015 1 m

990016 2 m

COVER HR

990056 1 m, satined

990057 2 m, satined



Delivery without accessories

HR - LINE

Information

- for LED lighting with flexible stripes up to 11,5 mm width
- for wall- and floor installation, walkable, passable max. load 1t (for high loads we recommend a foam cushioning pad to block under the profile; item 990095)
- for damp locations and lighting of indoor and outdoor areas (only suitable with the appropriate IP protection)

Application

- installation in cobblestone paths (driveways, parking lots)
- civil engineering, architecture, agriculture, light line mark in public spaces, building facades, swimming pools

mounting (not in range)


- concrete or mortar ceramic glue (elastic, frost resistant)

Ending (not in range)

- we recommend silicone glue (DOW CORNING 794, transparent)

Advantages

- designed to meet IP67 waterproof level
- homogeneous illumination because of deep-seated
- LED Stripes walkable/passable, good heat output, easy installation, light in weight, environmentally friendly, modern design



HR - LINE

aluminum

990013 1 m

990014 2 m

COVER HR

990054 1 m, satined

990055 2 m, satined

PROFIL COVER PLATE

990085 closed/piece

990086 with cable outlet



FOAM PAD (plastic rigid foam)

990095 124 cm

