



VLP2500 power amplifier

1141000012

SPECIFICATIONS

- Output Power:
 - 1100W RMS Per Channel @ 4 Ohms, 1kHz, 0.1% THD
 - 700W RMS Per Channel @ 8 Ohms, 1kHz, 0.1% THD
- Bridge Mode, Mono
 - 2200W RMS @ 8 Ohms, 1K Hz, 1% THD
- Total Harmonic Distortion: Less Than 0.5% (20Hz - 20kHz @ 8 Ohms)
- Frequency Response: (+/-01db, @rated output Power, 8 Ohms): 20Hz - 20K Hz
- Slew Rate: 20V Per usec
- Damping Factor: @ 8 Ohm: >450
- Impedance: 20 K Ohms balanced / 10 K Ohms unbalanced
- Cooling System: 2 individual fans (various speed)
- Special Features: High/Low Pass Filter/Input, Soft Start Sensitivity Selector/Ground Lift
- Output: Speaker + Binding post
- Dimensions (LxWxH): 453 x 482 x 88mm 2-rack mount space
- Weight: 22,6kg



VLP1500 power amplifier

1141000011

SPECIFICATIONS

- Output Power:
 - 675W RMS Per Channel @ 4 Ohms, 1kHz, 0.1% THD
 - 450W RMS Per Channel @ 8 Ohms, 1kHz, 0.1% THD
- Bridge Mode, Mono
 - 1400W RMS @ 8 Ohms, 1K Hz, 1% THD
- Total Harmonic Distortion: Less Than 0.1% (20Hz - 20kHz @ 8 Ohms)
- Frequency Response: (+/-01db, @rated output Power, 8 Ohms): 20Hz - 20K Hz
- Slew Rate: 15V Per usec
- Damping Factor: @ 8 Ohm: 300
- Impedance: 20 K Ohms balanced / 10 K Ohms unbalanced
- Cooling System: 2 individual fans
- Special Features: High/Low Pass Filter / Input Sensitivity Selector / Ground Lift; Limiter
 - build in clip limiter
- Input: XLR 3pin + Jack 6,3mm
- output: Speaker + Binding post
- Dimensions (LxWxH): 360 x 482 x 88mm 2-rack mount spaces
- Weight: 42 lbs. / 19 Kgs.



VLP1000 power amplifier

1141000013

SPECIFICATIONS

- Output Power:
 - 500W RMS Per Channel @ 4Ohms, 1kHz, 0.1%THD
 - 330W RMS Per Channel @ 8 Ohms, 1kHz, 0.1% THD
- Bridge Mode, Mono
 - 820W RMS @ 8 Ohms, 1K Hz, 1% THD
- Total Harmonic Distortion: Less Than 0.1% (20Hz - 20kHz @ 8 Ohms)
- Frequency Response: (+/-01db, @rated output Power, 8 Ohms): 20Hz - 20K Hz
- Slew Rate: 15V Per usec
- Damping Factor: @ 8 Ohm: 300
- Impedance: 20 Ohms balanced / 10 Ohms unbalanced
- Cooling System: 2 individual fans
- Special Features: High/Low Pass Filter / Input Sensitivity Selector / Ground Lift; Limiter
 - build in clip limiter
- Input: XLR 3pin + Jack 6,3mm
- output: Speaker + Binding post
- Dimensions (LxWxH): 360 x 482 x 88mm 2-rack mount spaces
- Weight: 15 Kgs.



VLP600 power amplifier

1141000010

SPECIFICATIONS

- Output Power:
 - 300W RMS Per Channel @ 4 Ohms, 1kHz, 0.1% THD
 - 200W RMS Per Channel @ 8 Ohms, 1kHz, 0.1% THD
- Bridge Mode, Mono
 - 600W RMS @ 8 Ohms, 1K Hz, 1% THD
- Total Harmonic Distortion: Less Than 0.1% (20Hz - 20kHz @ 8 Ohms)
- Frequency Response: (+/-01db, @rated output Power, 8 Ohms): 20Hz - 20K Hz
- Slew Rate: 15V Per usec
- Damping Factor: @ 8 Ohm: 300
- Impedance: 20 Ohms balanced / 10 Ohms unbalanced
- Cooling System: 2 individual fans
- Special Features: High/Low Pass Filter / Input Sensitivity Selector / Ground Lift Limiter
 - build in clip limiter
- Input: XLR 3pin + Jack 6,3mm
- output: Speaker + Binding post
- Dimensions (LxWxH): 360 x 482 x 88mm 2-rack mount spaces
- Weight: 33 lbs. / 15 Kgs.



VLP300 power amplifier

1141000009

SPECIFICATIONS

- Output Power:
 - 150W RMS Per Channel @ 4 Ohms, 1kHz, 0.1% THD
 - 100W RMS Per Channel @ 8 Ohms, 1kHz, 0.1% THD
- Bridge Mode, Mono
 - 300W RMS @ 8 Ohms, 1K Hz, 1% THD^
- Total Harmonic Distortion: Less Than 0.1% (20Hz - 20kHz @ 8 Ohms)
- Frequency Response: (+/-01db, @rated output Power, 8 Ohms): 20Hz - 20K Hz
- Slew Rate: 15V Per usec
- Damping Factor: @ 8 Ohm: 260
- Impedance: 20 Ohms balanced / 10 Ohms unbalanced
- Cooling System: 2 individual fans
- Special Features: High/Low Pass Filter/Input Sensitivity Selector/Ground Lift
- Input: XLR 3pin + Jack 6,3mm
- output: Speaker + Binding post
- Dimensions (LxWxH): 336 x 482 x 44mm 1-rack mount space
- Weight: 24 lbs.(11kg)

