

Sense Series

The SENSE SERIES by American Audio is a multifunctional, compact and lightweight speaker system for flexible yet ambitious sound applications. The HF cabinets' asymmetric design allows for both FoH and monitor usage. The passive crossovers are fine-tuned for optimum acoustics and excellent dynamics and have been developed using complex frequency curves and delays.

SENSE 8

1162220001

SPECIFICATIONS

- Woofer: 8" AA PA 850. Aluminium basket. 50mm voicecoil
- Hightession driver with 44mm voicecoil mounted on a 90°x60° CD hom
- Power Handling:
- 175W continuous
- 350W program 700W peak
- Recommended input power: 100-250W @ 8Ohm
- Sensitivity:
- 3dB SPI
- 121dB Peak
- Freq. response: (-3dB) 88Hz 20kHz
- Freq. range: (-10dB) 75 Hz 21kHz
- Nom. dispersion h x v: (-6dB) 90°x60°
- Impedance: 80hm
- X-Over: 2800 Hz 12dB/18dB
- Finish: black structure paint
- Protective Grid: powder coated steel grill with acoustic foam
- Connector: 2x NL4 Speaker
- Handle: 1 handle on the top
- Monitor angle: 45°
- Pole mount: integrated M10 Screws for rigging eves in all corners
- cabinet: plywood
- Dimensions (LxWxH): 250x436x230mm
- Weight: 10kg

FEATURE OVERVIEW

- Perfect matched components and case details
- Passive full range system for medium size applications
- Multifunctional case design
- Quadratic horn (rotatable)
- 90° x 60° dispersion
- First class mechanical manufacture for day-to-day
- Equipped with optimized 8" MF/LF driver
- Large optional accessory range
- . Ideal for mobile and install applications

SENSE 12 1162240001

SPECIFICATIONS

- Woofer: 12" AA PA1575, aluminium basket, 75mm
- High Driver: 1" compression driver with 44mm (1.75") voicecoil mounted on a 75°x50° CD Horn
- Power Handling:
- 350W continuous
- 700W program 1400W peak
- Recommended input power: 250-500W @ 8Ohm
- Sensitivity
- 98dB SPL max
- 128dB Peak
- Freq. response (-3dB): 59Hz 20kHz
- Freq. range(-10dB): 51 Hz 21kHz
- Nom. dispersion h x v (-6dB): 75°x50°
- Impedance: 80hm
- X-Over: 1800 Hz 12dB/18dB
- Finish: black structure paint
- Protective Grid: powder coated steel grill with acoustic foam
- Connector: 2x NL4 Speaker
- Handle: 1 handle on the top
- Monitor angle: 45°
- Pole mount: integrated
- M10 Screws for rigging eyes in all corners
- Cabinet: plywood
- Dimensions (LxWxH): 360x640x325mm
- Weight: 18kg

FEATURE OVERVIEW

- Perfect matched components and case details
- Passive full range system for medium size applications
- Multifunctional case design
- Rotatable horn
- 75° x 50° dispersion
- First class mechanical manufacture for day-to-day
- Equipped with optimized 12" MF/LF driver
- Large optional accessory range
- Ideal for mobile and installed applications

SENSE 15 1162250001

SPECIFICATIONS

- Woofer: 15" AA PA1575, aluminium basket, 75mm voicecoil
- High Driver: 1" compression driver with 44mm (1.75") voicecoil on a 75°x50° CD hom
- Power Handling:
- 400W continuous
- 800W program
- 1600W peak
- Recommended input power: 300-600W @ 8Ohm
- Sensitivity: 98dB SPLmax. 129dB Peak
- Freq. response (-3dB): 52Hz 20kHz
- Freq. range(-10dB): 42Hz 21kHz
- Nom. dispersion h x v (-6dB): 75°x50° Impedance: 80hm
- X-Over: 1800 Hz 12dB/18dB Finish: black structure paint
- Protective Grid: powder coated steel grill acoustic foam
- Connector: 2x NL4 Speaker
- Handle: 1 handle on the top
- Monitor angle: 45°
- Pole mount: integrated, M10 Screws for rigging eyes in all corners
- Cabinet: plywood
- Dimensions (LxWxH): 430x678x370mm
- Weight: 22kg

FEATURE OVERVIEW

- Perfect matched components and case details
- Passive full range system for medium size applications
- Multifunctional case design
- Quadratic horn (rotatable)
- 75° x 50° dispersion
- First class mechanical manufacture for day-to-day operations
- Equipped with optimized 15" MF/LF driver
- Large optional accessory range
- . Ideal for mobile and install applications

COVER SENSE 12 SPEAKER

COVER SENSE 15 SPEAKER