



SENSE 215

1162250004

SPECIFICATIONS

- Woofer: 15" AA PA1575, aluminum basket, 75 mm voice coil
- HF Driver: 1" compression driver with 44 mm (1.75") voice coil on a 75°x50° horn
- Power Handling:
800W continuous
1600W program
3200W peak
- Recommended input power: 600...1200W at 4 Ohms
- Sensitivity: 101dB, SPLmax: 135dB peak
- Frequency response (-3dB): 60Hz - 19kHz
- Frequency range (-10dB): 45Hz - 21kHz
- Nom. Dispersion h x v (-6dB): 75° x 50°
- Impedance: 4 Ohms
- X-Over: 1800Hz 12dB / 18dB
- Finish: black structure paint
- Protective grille: powder coated sheet steel, acoustic foam
- Connector: 2x NL4 Speaker
- Handle: 2 handles in enclosure sides
- Mounting: threaded inserts for M10 screws in all enclosure corners
- Cabinet construction: Braced birch plywood
- Dimensions (L x W x H): 430 x 465 x 1110mm
- Weight : 36,9kg

SENSE 15B Subwoofer

1162270002

SPECIFICATIONS

- Woofer: 15" AA PA15000, aluminum basket, 100mm Voicecoil
- Power Handling
450W continuous
900W program
1800W peak
- Recommended input power: 300-600 W @ 8Ohm
- Components: 15" Long excursion woofer
- Sensitivity (Half Space):
102dB SPL
135dB Peak
- Freq. response (-3dB): 45Hz - 200Hz
- Freq. range(-10dB): 40Hz - 250Hz
- Impedance: 8Ohm
- Finish: black structure paint
- Protective Grid: powder coated steel grill with acoustic foam
- Connector: 2x NL4 Speaker
- Handle: 2 handles on the sides
- Pole mount: integrated (M20)
- Cabinet: plywood
- Dimensions (LxWxH): 430x550x550mm
- Weight: 26,5kg

FEATURE OVERVIEW

- Perfect harmonized components and case details
- High efficiency
- First class mechanical manufacture for day-to-day operations
- Equipped with optimized 15" LF driver
- Large optional accessory range
- Ideal for mobile and install applications

COVER SENSE 15B SPEAKER

Code: 1163100010

SENSE 18B Subwoofer

1162270003

SPECIFICATIONS

- Woofer: 18" AA PA18000, aluminum basket, 100mm Voicecoil
- Power Handling
600W continuous
1200W program
2400W peak
- Recommended input power: 400-800 W @ 8Ohm
- Components: 18" Longexcursion woofer
- Sensitivity (Half Space):
103dB SPL
136dB Peak
- Freq. response (-3dB): 42Hz - 200Hz
- Freq. range(-10dB): 36Hz - 250Hz
- Nom. dispersion h x v (-6dB): 90°x60°
- Impedance: 8Ohm
- Finish: black structure paint
- Protective Grid: powder coated steel grill with acoustic foam
- Connector: 2x NL4 Speaker
- Handle: 2 handles on the sides
- Pole mount: integrated (M20)
- Cabinet: plywood
- Dimensions (LxWxH): 520x650x600mm
- Weight: 33kg

FEATURE OVERVIEW

- Perfect matched components and enclosure details
- High efficiency
- First class mechanical manufacture for day-to-day operations
- Equipped with optimized 18" LF driver
- Large optional accessory range
- Ideal for mobile and install applications

COVER SENSE 18B SPEAKER

Code: 1163100011

